

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**



Eur päisches Pat ntamt  
European Patent Office  
Office européen n des brevets

(11) Publication number:

**0 326 497**  
**A2**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number: 89400241.9

(51) Int. Cl.<sup>4</sup>: **A 61 B 1/24**  
**A 61 B 1/04**

(22) Date of filing: 27.01.89

(30) Priority: 28.01.88 US 149521

(43) Date of publication of application:  
02.08.89 Bulletin 89/31

(84) Designated Contracting States: DE FR GB IT

(71) Applicant: FUJI OPTICAL SYSTEMS, INC.  
170 Knowles Drive  
Los Gatos California 95030 (US)

(72) Inventor: Cooper, David H.  
13668 Ronnie Way  
Saratoga California 95070 (US)

Bush, Charles S.  
15466 Los Gatos Boulevard  
Los Gatos California 95030 (US)

(74) Representative: Martin, Jean-Jacques et al  
Cabinet REGIMBEAU 26, Avenue Kléber  
F-75116 Paris (FR)

(54) Electronic video dental camera and dental instrument.

(57) An electronic video dental camera is provided which overcomes the disadvantages of both prior art dental mirrors, endoscopes, and video endoscopes. The electronic video dental camera is readily manipulated by dentists who are familiar with the manipulation of dental mirrors. Such an electronic video dental camera includes a handle to be held by the user, and a camera head located at the distal end of the handle, with the camera head being formed at an angle to the handle, as in prior art dental mirrors. One embodiment includes provision for the flow of a selected fluid in order to defog and/or clean the camera lens. In one embodiment, the camera head includes light sources for illuminating the area to be viewed. In one embodiment, the handle of the dental camera includes means for transporting all appropriate signals and fluids to and from the camera head, and, if desired, valves and switching means located on the handle for controlling such communication to the camera head. One embodiment includes a dental camera head which allows a number of attachments to be used, such as a telephoto lens, wide angle lens, relay lens, and transillumination devices. In an alternative embodiment, the dental camera is attached to another dental instrument, such as a dentist's drill;




FIG. 6

**0 326 497 A2**

## Description

## ELECTRONIC VIDEO DENTAL CAMERA AND DENTAL INSTRUMENT

BACKGROUND OF THE INVENTION

This invention is an electronic video dental camera having a handle and head for use in placement in a dental patient's mouth, and allowing areas within the mouth be displayed via a video signal.

More precisely, the invention relates to improvements to the electronic video dental camera defined in EP-A-0,280,823.

SUMMARY OF THE INVENTION

In accordance with the teachings of this invention, an electronic video dental camera is provided which overcomes the disadvantages of both prior art dental mirrors, endoscopes, video endoscopes and electronic video dental cameras.

The electronic video dental camera and the dental instrument of this invention are defined in the appended claims.

In one embodiment of this invention, the handle is uniquely designed to include electronics, such as video amplifiers and imaging device driver circuitry, thereby eliminating the need to include this circuitry in the camera head itself. In an alternative embodiment of this invention, elements of this electronic circuitry is located in the cable, or connectors, or in the video processor unit itself.

One embodiment includes a dental camera head which allows a number of attachments to be used, such as a telephoto lens, wide angle lens, relay lens, and transillumination devices. In an alternative embodiment of this invention, the dental camera is attached to another dental instrument, such as a dentist's drill, thereby allowing video monitoring of the task being performed by the dentist. In yet another embodiment of this invention, the dental camera is formed as an integral part of the dental instrument, such as dental drill.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram depicting the use of an electronic video dental camera system constructed in accordance with the teachings of EP-A-0,280,823;

Fig. 2 is a cross sectional view of one embodiment of a video dental camera constructed in accordance with the teachings of EP-A-0,280,823;

Fig. 3 is a plan view of one embodiment of a camera head constructed in accordance with the teachings of EP-A-0,280,823;

Fig. 4 is a cross sectional view of one embodiment of a camera head constructed in accordance with the teachings of EP-

A-0,280,823;

Fig. 5 is a block diagram depicting a dental camera system constructed in accordance with the teachings of this invention;

Fig. 6 is a diagram depicting a dental camera constructed in accordance with the teachings of this invention depicting where certain electronics may be conveniently located;

Fig. 7 depicts one embodiment of a dental camera constructed in accordance with the teachings of this invention which includes a dental camera head designed for receiving one of a plurality of attachments, such as the wide angle lens shown in Fig. 7;

Figs. 7a, 7b and 7c depict a telephoto lens, a relay lens, and an alternative embodiment of a relay lens, respectively, suitable for use with the dental camera head of Fig. 7;

Fig. 8 is an alternative embodiment of a dental camera head constructed in accordance with the teachings of this invention which allows one of a plurality of attachments to be used, and a wide angle lens serving as such an attachment;

Figs. 8a and 8b depict a telephoto lens, and a relay lens, respectively, suitable for use with the camera head of Fig. 8;

Figs. 9a through 9f depict various embodiments of a transillumination device constructed in accordance with the teachings of this invention;

Fig. 10 depicts one embodiment of a dental camera constructed in accordance with the teachings of this invention and which is attached to a dental instrument;

Fig. 11 is an alternative embodiment of a dental camera attached to a dental instrument; and

Fig. 12 is a view of one embodiment of a dental camera constructed in accordance with the teachings of this invention which is integrally formed with a dental instrument.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 shows the use of a dental camera 10 constructed in accordance with the teachings of EP-A-0,280,823. Video processor and control means 8 serves to provide power, light and, if desired, fluid and other appropriate signals via cable 7 to dental camera 10. Video processor and control means 8 provides a video signal to video monitor 6 in order that users may view a location within a patient's mouth by way of dental camera 10. If desired, foot switch 9 is used to provide a signal to video processor and control means 8 indicating when air and/or fluids are to be sent by video processor and control means 8 to dental camera 10.

Fig. 2 shows a cross section of one embodiment of a video dental camera constructed in accordance with the teachings of EP-A-0,280,823. Video dental

camera 10 includes body 16 having handle 11 suitable for being held by an operator, and, if desired having forward extension 13. At one end of handle 11 is located connector 12 for connection, via a cable assembly (not shown) to video processor and control unit 8 (Fig. 1). If desired, forward extension 13 and handle 11 have generally circular cross section, although other suitable shapes, such as octagonal, and polygonal can be used. The important point is that handle 11 should be easily and comfortably gripped by the user, and forward extension 13 should be of a general size and cross section which is convenient for insertion into the patient's mouth and, of course, comfortable for the patient.

Located at the distal end of forward extension 13, and mounted on forward extension 13 at an angle A to forward extension 13, is camera head 14. Face 15 of camera head 14 includes means for receiving an image within a patient's mouth to be displayed on a video monitor. In one embodiment of EP-A-0,280,823, such means for receiving the image is fiber optic tubes or one or more rod lens assemblies or a combination thereof with or without additional lenses, which transmit the image to an image sensor (not shown) either within forward extension 13, body 16 or, in another embodiment of EP-A-0,280,823, the image is transmitted by one or more rod lens assemblies or fiber optic cable, or a combination thereof with or without additional lenses, through connector 12 to an image sensor located in external video equipment (not shown). However, in a preferred embodiment the image sensor is located directly in camera head 14 and receives the image from the patient's mouth via a lens, without the need for fiber optics.

Fig. 3 shows a cross sectional phantom view of camera head 14. In this embodiment, fiber optic light guides 30a and 30b are used to receive light from a light source (not shown) which may comprise, for example a halogen lamp or a Xenon arc lamp located at the proximal end of light guides 30a and 30b, and conduct this light through fiber optic curvatures 31a and 31b to illumination lenses 32a and 32b respectively. Also shown in Fig. 3 is image lens 33 and image sensor 35 which is mounted on hybrid assembly substrate 36 located within cavity 37. As shown in Fig. 3, in one embodiment of EP-A-0,280,823, the center of the ends of fiber optic light pipes 30a and 30b are offset from the center of illumination lenses 32a and 32b, respectively, in a direction toward image lens 33. This causes the light being emitted from fiber optic light pipes 30a and 30b to be directed toward the image being viewed. Also, in one embodiment of EP-A-0,280,823 illumination lenses 32a and 32b are dispersion lenses which include a "frosting" to disperse the light. Image sensor 35 is connected to video control cable 34 which communicates power and control signals to image sensor 35 and communicates video signals to the video processor and control means 8 of Fig. 1. As an alternative embodiment, a third fiber optic cable or a rod lens assembly (not shown) is used to conduct the image from image lens 33 to an image sensor located in forward extension 13, handle 11, or

via connector 12 (Fig. 2) to an image sensor located external to dental camera 10.

Fig. 4 shows a cross sectional phantom view of the structure shown in Fig. 3, with elements numbered in a similar fashion. Thus, shown in Fig. 4 are fiber optic light guide 30, fiber optic curvature 31 and illumination lens 32. In one embodiment, illumination lens 32 is a dispersion lens which serves to properly distribute the light over a wider angle and area upon exit from fiber optic light guide 30, to correspond to the field of view of image lens 33. Fig. 4 also shows image lens 33 located within camera head 14 between camera head face 15 and image sensor 35. In the embodiment shown in Fig. 4, image lens 33 is affixed directly to image sensor 35. In an alternative embodiment of EP-A-0,280,823, image lens 33 is affixed to the body of camera head 14, and image sensor 35 is also affixed, via substrate 36, to the body of camera head 14, thereby maintaining image lens 33 and image device 35 in fixed relationship. In another embodiment of EP-A-0,280,823, fiber optic curvature 31 is not used, but is replaced by a prism or mirror assembly which serves to reflect light from fiber optic light guide 30 to face 15 of camera head 14. If desired, a suitable lens can be placed on the fiber optic side of the prism or mirror, or on the face 15 side of the prism or mirror, or in both locations, if desired.

In one embodiment of EP-A-0,280,823 an infrared filter is placed between the light source (not shown) and fiber optic light guide 30. This infrared filter serves to prevent damage to fiber optic light guide 30 by masking out damaging infrared rays from the light source. In another embodiment of EP-A-0,280,823, color filters are used as desired. For example, color filters can be placed anywhere between the light source and illumination lens 32 in order to selectively apply desired colors of illumination to the image being viewed. Alternatively, one or more color filters can be placed between image lens 33 and image sensor 35, again in order to selectively remove desired colors of the image being presented to image sensor 35. In yet another embodiment, an infrared blocking filter is placed in the image path between the image being viewed and image sensor 35 in order to prevent infrared energy from being applied to image sensor 35. This is particularly useful, for example, when a dentist is using a laser to perform certain dental procedures during which time a relatively larger amount of infrared energy is present. If not blocked out, this infrared energy would be detected by image sensor 35, resulting in a "washed out" video signal.

In one embodiment of EP-A-0,280,823, forward extension 13 includes fluid jet 39 (Fig. 4) which serves to allow fluid to be introduced across face 15 of camera head 14. In this manner, for example, a constant or pulsed flow of gas, such as air, can be made to provide a laminar flow across image lens 33 to prevent fogging. If desired, a liquid such as water can be introduced as well in order to clean image lens 33. Fluid jet 39 can also be placed in any convenient location.

Fig. 5 is a block diagram of the electronics portion of a dental camera which includes image device 60

such as a charge coupled device (CCD), image device driver buffer 61 which serves to control image device 60, video amplifier circuitry 62, and video processor 8 for controlling driver buffer 61 and processing the video information which is then presented to display 6. For best results, driver buffer 61 and video amplifier 62 are located very close to image device 60 in order to maintain the necessary drive pulse waveforms and timing relationships, and insure the optimum frequency response of the video image. Ideally, these circuits are fabricated on the same integrated circuit as imaging device 60. Alternatively, driver buffer 61 and video amplifier 62 are formed as individual components in a hybrid or printed circuit board assembly with imaging device 60. However, in certain embodiments of this invention, this is not possible due to size limitations of the dental camera head 15 (Fig. 1). Also, the heat generated by driver buffer 61 and video amplifier 62 can, in certain instances, impair the operation of the imaging device 60, for example by raising the dark current.

In one embodiment of this invention, driver buffer 61 and video amplifier 62 are located as either individual circuits, a single integrated circuit, or a hybrid assembly, located in any convenient location within the dental camera. Such convenient locations are handle 11, forward extension 13, or within connecting cable 7 (Fig. 1).

Fig. 6 is a drawing of one embodiment of a dental camera constructed in accordance with the teachings of this invention. As shown in Fig. 6, circuitry 101 may be included within handle 11. Circuitry 101 can include one or both driver buffer 61 and video amplifier 62 (Fig. 5), and can be formed either as an integrated circuit, hybrid device, or components located on a printed circuit board or the like. If desired, circuitry 101 includes an imaging device which receives visible light via, for example, a rod lens assembly or one or more optical fibers (not shown) which serve to transport the image from dental camera head 14 to circuitry 101.

In an alternative embodiment of this invention, electronics as described above may be located within cable 201, connector assembly 203, cable 204, connector 205, or within processing unit 8 (Fig. 5). Alternatively, various portions of the electronics can be conveniently located within a plurality of locations shown in Fig. 6.

Fig. 7 is a diagram of a dental camera constructed in accordance with the teachings of this invention which includes provisions in head 14 for mounting an external device. In one embodiment of this invention, a dental camera is provided which allows for such external devices to be removed and interchanged, thereby allowing a single dental camera to serve a wide number of uses.

In accordance with the teachings of this invention, a number of possible external devices are provided, included but not limited to a wide angle lens as shown in Fig. 7, a telephoto lens as shown in Fig. 7a, a rod lens or one or more fiber optic cables serving as a "relay lens" as shown in Fig. 7b. Such a telephoto lens of Fig. 7a is very convenient for viewing very small areas, for example for use in

viewing the capillaries within the gums, thereby allowing the dentist or oral surgeon to determine the relative health of the gums by determining the condition of blood circulation within the gums. Such a telephoto lens is also useful for obtaining a frontal view of the entire mouth, by holding the telephoto lens at an appropriate distance from the patient's face. Use of a telephoto lens for this purpose avoids the frontal image of the patient's mouth appearing as a "fish eye" view. A relay lens as in Figs. 7b and 7c is highly suitable for viewing the small spaces between the teeth more readily than can be viewed using the dental camera itself. Each of these examples in Figs. 7, 7a, and 7b include provisions for providing light to the area to be imaged. These take the form of additional lenses or windows 102 which optimize the area and uniformity of illumination to correspond to the angle of view of the lens being used. Alternatively, a relay lens as shown in Fig. 7c is provided, in which, for example, an optical fiber is used to both transmit light to the area to be imaged, and transmit the image to the dental camera imaging device contained within dental camera head 14. Filter attachments and lens/filter combinations can also be used. For example, infrared filters can be used to block infrared energy emitted by a laser during surgery, thereby allowing proper viewing of the surgery in process. Alternatively, color filters can be placed in the path of the light being emitted by the light source in order to selectively apply desired colors of illumination to the image being viewed. Alternatively, filters can be placed in the path of the light being received by the image device in order to selectively remove desired colors of the image being present to the image sensor.

Figs. 8, 8a, and 8b show alternative embodiments of the wide angle, telephoto, and relay lenses, respectively, which are capable of being clipped on to dental camera head 14 which includes slots 105 for reception of attachment bracket 106. Filters can also be used as described above with regard to Fig. 7.

Figs. 9a through 9d depict various embodiments of a dental camera constructed in accordance with the teachings of this invention suitable for transillumination of an area to be examined. For example, in the embodiments of Fig. 9a and Fig. 9c, illumination means 30, such as an optical fiber, receives light from a light source within camera head 14 (or via means which carries light to camera head 14), and provides this light via, for example, optical fibers or a rod lens, to the opposite side of the area being examined, for example a tooth, thereby allowing the tooth to be transilluminated and the image provided to the dental camera head being that of the transilluminated tooth. Alternatively, this transillumination technique will allow the exterior of the tooth to be illuminated, and the interior of the tooth to be viewed, for example to view a cavity within the tooth, or the root canal. In one embodiment of this invention, illumination means 30 are malleable in order to allow their position with respect to camera head 14 to be altered, as desired.

As shown in the embodiments of Figs. 9b and 9d, light is emanated from camera head 14 for transil-

lumination of an area to be viewed, and the transilluminated image is received by means 38, such as one or more optical fibers, or a rod lens, for transmission to the imaging device within the dental camera. In one embodiment of this invention, means 38 is malleable to allow its position relative to camera head 14 to be altered, as desired.

In an alternative embodiment of this invention, as shown in Fig. 9e, a separate transillumination light source 130 is used, which is attached to camera body 16 by attachment means 131. If desired, attachment means 131 can allow the position of transillumination light source 130 to be changed relative to camera head 14. In this embodiment, camera head 14 either does not include light sources, or the light sources contained within camera head 14 are turned off during the use of transillumination light source 130.

Fig. 9f depicts an alternative embodiment of a transillumination device constructed in accordance with the teachings of this invention. As shown in Fig. 9f, camera head 14 includes a central cavity 220 which is placed in order to house the object to be transilluminated. On the interior walls of transillumination head 14 is included optical ports 230 and 231, either one of which may be the source of transillumination light, with the opposite optical port serving as the port for receiving the transilluminated image.

In another embodiment of this invention (Fig. 10), a rod lens or one or more optical fibers 91 are used for attaching the dental camera directly to a dentist's drill 92, thereby allowing the operation being performed by the dentist using his drill to be viewed on a video monitor. In an alternative embodiment shown in Fig. 11, a dental camera 10 is mounted to a dental drill 92, for example, by means of one or more clips or ties 98. In yet another embodiment of this invention, as shown in Fig. 12, the dental camera and dental drill are combined in a single instrument including camera head 14a attached to the end of dental drill/camera 92a. In one embodiment of this invention, camera head 14a includes an imaging device. In an alternative embodiment of this invention, camera head 14a includes means for receiving image, such as a fiber optic or a rod lens assembly, for transmission to an imaging device located within drill/camera 92a, or to the cable (not shown) or processor (not shown) attached to drill/camera 92a.

All publications and patent applications are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference. The invention now being fully described, it will be apparent to one of ordinary skill in the art that many changes and modifications can be made thereto without departing from the spirit or scope of the appended claims.

## Claims

1. A dental camera for use in displaying an image from inside the mouth onto a monitor comprising an electronic video endoscope comprising :

- an handle ;
- a camera head at the distal end of said handle including a means for receiving an image, said camera head being formed such that said means for receiving an image is placed at an angle from the axis of said handle ; and
- electronic circuitry contained within said handle.

2. A dental camera for use in displaying an image from inside the mouth onto a monitor comprising an electronic video endoscope comprising ;

- a handle ;
- a camera head at the distal end of said handle, including a transillumination device.

3. A dental camera for use in displaying an image from inside the mouth onto a monitor comprising an electronic video endoscope comprising :

- an handle ;
- a camera head at the distal end of said handle including a means for receiving an image, said camera head being formed such that said means for receiving an image is placed at an angle from the axis of said handle ; and
- a lens which is removably connected to said camera head.

4. A dental camera as in one of claims 1 to 3 comprising a camera head including means for receiving an image which is selected from the group of mirrors, lenses, optical fibers and filters.

5. A dental camera as in one of claims 1 to 4 comprising a camera head including an image device and electronic circuitry including one or more drivers for controlling said image device or amplifiers for amplifying signals received from said image device.

6. A dental camera as in one of claims 1 to 5 which further comprises a light source for illuminating an area to be viewed.

7. A dental camera as in one of claims 1 to 6, further comprises a camera lens which is removably connected to said camera head.

8. A dental camera as in claim 7, wherein said camera lens is selected from the group of camera lenses consisting of wide angle, telephoto, and relay lenses.

9. A dental camera as in claim 7 or 8 wherein said camera lens comprises an additional means for providing light toward the area being viewed by said camera head.

10. A dental camera as in claim 9, wherein said additional lens means comprises a transillumination device.

11. A dental camera as in claim 10, wherein said transillumination device comprises means for projecting light from said camera head, and said means for receiving an image receives said from the opposite side of the object being viewed.

12. A dental camera as in claim 10 or 11 wherein said transillumination device comprises means for illuminating the exterior of a tooth and means for receiving an image from within

said tooth.

13. A dental camera as in one of claims 1 to 12 which further comprises a filter located in the path of said received image.

14. A dental camera as in claim 13 wherein said filter is located between said means for receiving an image and said image device.

15. A dental camera as in claims 6, 11 or 12 which further comprises a filter in the path of the light from said light source.

16. A dental camera as in claims 13, 14 or 15 wherein said filter is an infrared filter.

17. A dental camera as in claims 13, 14, 15 or 16 wherein said filter is removably connected to said camera head.

18. A dental camera as in one of claims 1 to 17 comprising transillumination device including means for receiving an image and means for providing light to the opposite side of the object being viewed.

19. A dental camera as in claim 12 or 18 wherein said means for providing light comprises a rod lens or an optical fiber.

20. A dental camera as in claim 12, 18 or 19 wherein said means for providing light is

malleable.

21. A dental camera as in claim 2 wherein said camera head includes an image device.

22. A dental camera as in claim 10 wherein said transillumination device comprises a camera lens for providing an image to said camera head and light means for providing light to the opposite side of the object being viewed.

23. A dental instrument such as a dental drill, comprising a dental camera.

24. A dental instrument as in claim 23 wherein said dental camera comprises :

- a handle ; and
- a camera head at the distal end of said handle including a means for receiving an image , said camera head being formed such that said means for receiving an image is placed at an angle from the axis of said handle.

25. A dental instrument as in claim 24 further comprising electronic circuitry contained within said handle.

26. A dental instrument as in one of claims 23 to 25, comprising a dental camera as in one of claims 1 to 22.

30

35

40

45

50

55

60

65





FIG. 1

FIG. 2









FIG. 3




FIG. 4





FIG. 5






FIG. 6

# INTERCHANGEABLE LENSES



TELEPHOTO

FIG. 7a



RELAY LENS

FIG. 7b





FIG. 7



DETAIL A





FIG. 7c



CLIP ON LENSES

TELEPHOTO





FIG. 8a



WIDE

106

FIG. 8




FIG. 8b  
RELAY LENS




FIG. 9a




FIG. 9b





FIG. 9c






FIG. 9f






FIG. 9e




VIDEOPROBE / HANDPIECE

FIG. 10



DENTALCAMERA / HANDPIECE

FIG. 11



VIDEO HANDPIECE

FIG. 12



⑫

**EUROPEAN PATENT APPLICATION**

⑰ Application number: 89400241.9

⑤ Int. Cl.<sup>4</sup>: **A 61 B 1/24**  
**A 61 B 1/04**

⑱ Date of filing: 27.01.89

③① Priority: 28.01.88 US 149521

④③ Date of publication of application:  
02.08.89 Bulletin 89/31

④④ Designated Contracting States: DE FR GB IT

④⑧ Date of deferred publication of search report:  
11.10.89 Bulletin 89/41

⑦① Applicant: **FUJI OPTICAL SYSTEMS, INC.**  
170 Knowles Drive  
Los Gatos California 95030 (US)

⑦② Inventor: **Cooper, David H.**  
13668 Ronnie Way  
Saratoga California 95070 (US)

**Bush, Charles S.**  
15466 Los Gatos Boulevard  
Los Gatos California 95030 (US)

⑦④ Representative: **Martin, Jean-Jacques et al**  
Cabinet REGIMBEAU 26, Avenue Kléber  
F-75116 Paris (FR)

⑤④ **Electronic video dental camera and dental instrument.**

⑤⑦ An electronic video dental camera (10) includes a handle (11) to be held by the user, and a camera head (14) located at the distal end of the handle (11), with the camera head (14) being formed at an angle to the handle (11), as in prior art dental mirrors. One embodiment includes provision for the flow of a selected fluid in order to defog and/or clean the camera lens (33). In one embodiment, the camera head (14) includes light sources (32a,b) for illuminating the area to be viewed. In one embodiment, the handle (11) of the dental camera (10) includes means for transporting all appropriate signals and fluids to and from the camera head (14), and, if desired, valves and switching means located on the handle for controlling such communication to the camera head. One embodiment includes a dental camera head (14) which allows a number of attachments to be used, such as a telephoto lens, wide angle lens, relay lens, and transillumination devices. In an alternative embodiment, the dental camera (10) is attached to another dental instrument, such as a dentist's drill (92), thereby allowing video monitoring of the task being performed. In another embodiment, the dental camera is formed as an integral part of the dental instrument.



EP 89 40 0241

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
Y	DE-A-2 208 902 (RITTER AG) * Figure 1; page 4, lines 2-25 * ---	1-3,6, 23-26	A 61 B 1/24 A 61 B 1/04
Y	US-A-4 491 865 (DANNA et al.) * Figure 2; column 2, line 18 - column 3, line 48 * ---	1-3,23-26	
A	---	4-6,15,21	
Y	US-A-4 468 197 (PROVOST) * Figures 1,2; column 3, line 27 - column 4, line 48; column 5, lines 36-64 * ---	2	
A	---	4,10-12,18,19	
A	DE-A-3 716 401 (OHKUWA) * Figures 3-7; column 2, lines 52-67; column 3, line 54 - column 6, line 11 * ---		
A	EP-A-0 122 537 (SUMITOMO ELECTRIC INDUSTRIES LTD) * Figures 2-7; page 5, line 2 - page 9, line 8 * ---	1-4,9	TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
A	DE-A-3 233 410 (SCHÖLLY) * Figures 3,7,8; page 10, line 7 - page 11, line 27; page 13, line 16 - page 14, line 14 * ---	20	A 61 B
A	EP-A-0 066 901 (VOLPI AG) * Figure 1; page 4, line 15 - page 5, line 16 * --- -/-	15,16	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14-07-1989	Examiner CHEN A.H.
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			



European Patent  
Office

# EUROPEAN SEARCH REPORT

Page 2

Application Number

EP 89 40 0241

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
D, P A	EP-A-0 280 823 (FUJI OPTICAL SYSTEMS INC.) * Figures 1-5; column 3, line 3 - column 6, line 14 * -----	1, 4, 13-16, 19	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14-07-1989	Examiner CHEN A.H.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons			

RM 1503 03.82 (P0401)